

Package: epiworldRcalibrate (via r-universe)

June 1, 2026

URL <https://sima-njf.github.io/epiworldRcalibrate/>,
<https://github.com/sima-njf/epiworldRcalibrate>

BugReports <https://github.com/sima-njf/epiworldRcalibrate/issues>

Title Fast and Effortless Calibration of Agent-Based Models using
Machine Learning

Version 0.1.3

Description Provides tools and pre-trained Machine Learning [ML] models for calibration of Agent-Based Models [ABMs] built with the R package 'epiworldR'. Implements methods described in Najafzadehkhoei, Vega Yon, Modenesi, and Meyer (2025) <[doi:10.48550/arXiv.2509.07013](https://doi.org/10.48550/arXiv.2509.07013)>. Users can automatically calibrate ABMs in seconds with pre-trained ML models, effectively focusing on simulation rather than calibration. Bridges a gap by allowing public health practitioners to run their own ABMs without the advanced technical expertise often required by calibration.

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

Suggests testthat (>= 3.0.0), epiworldR

Config/testthat/edition 3

Imports reticulate (>= 1.41), utils

Depends R (>= 3.5)

LazyData true

Config/pak/sysreqs libpng-dev python3

Repository <https://sima-njf.r-universe.dev>

Date/Publication 2026-04-02 18:03:27 UTC

RemoteUrl <https://github.com/sima-njf/epiworldrcalibrate>

RemoteRef HEAD

RemoteSha f8a39ce2cbda363fec0d8c10067c3baf45db3938

Contents

abc_calibration_params	2
calibrate_sir	3
check_model_status	4
check_python_setup	4
cleanup_model	4
estimate_sir_parameters	5
init_bilstm_model	5
setup_python_deps	6
utah_covid_data	7
Index	8

abc_calibration_params

ABC calibration results for COVID-19 SIR model

Description

Results from Approximate Bayesian Computation (ABC) calibration of an SIR network model fitted to Utah COVID-19 incidence data.

Usage

abc_calibration_params

Format

A named list with the following elements:

contact_rate Posterior median of the contact rate.

recovery_rate Posterior median of the recovery rate.

transmission_prob Posterior median of the transmission probability.

R0 Basic reproduction number computed from posterior medians.

contact_rate_ci 95 percent credible interval for the contact rate.

recovery_rate_ci 95 percent credible interval for the recovery rate.

transmission_prob_ci 95 percent credible interval for the transmission probability.

calibration_time_seconds Total runtime of the ABC calibration (seconds).

n_samples Number of MCMC samples used in calibration.

burnin Number of burn-in iterations discarded.

epsilon ABC tolerance parameter.

seed Random seed used for reproducibility.

posterior_samples Matrix of post-burn-in accepted parameter samples.

acceptance_rate Acceptance rate of the ABC-MCMC algorithm (percent).

Source

Generated internally using the script `data-raw/process_covid_calibration.R`.

Examples

```
data("abc_calibration_params")
str(abc_calibration_params)
```

 calibrate_sir

Calibrate SIR Parameters (one-step convenience wrapper)

Description

Optionally initializes the BiLSTM model and then calls `estimate_sir_parameters` on the provided data.

Usage

```
calibrate_sir(
  daily_cases,
  population_size,
  recovery_rate,
  model_dir = NULL,
  auto_init = TRUE
)
```

Arguments

<code>daily_cases</code>	Numeric vector of length 61 containing daily incidence counts (day 0 to day 60).
<code>population_size</code>	Single numeric value giving the total population size.
<code>recovery_rate</code>	Single numeric value giving the recovery rate parameter.
<code>model_dir</code>	Optional path to the directory containing the trained BiLSTM model and scaler files. If NULL, the package's bundled assets are used.
<code>auto_init</code>	Logical; if TRUE (default), automatically calls <code>init_bilstm_model</code> when the model is not yet loaded.

Value

Named numeric vector: `ptran`, `crate`, `R0`.

check_model_status *Check model status*

Description

Check model status

Usage

check_model_status()

Value

A list describing model load status and Python config.

check_python_setup *Check Python and package installation status*

Description

Reports whether Python is available, which package-managed Python target is in use, and whether each required Python package is importable.

Usage

check_python_setup()

Value

A list with Python runtime details and package status.

cleanup_model *Unload the model from memory*

Description

Unload the model from memory

Usage

cleanup_model()

Value

Invisibly TRUE on success.

`estimate_sir_parameters`*Estimate SIR Parameters from 61-day incidence*

Description

Estimate SIR Parameters from 61-day incidence

Usage

```
estimate_sir_parameters(daily_cases, population_size, recovery_rate)
```

Arguments

`daily_cases` Numeric vector of length 61 containing daily incidence counts for days 0 to 60.
`population_size` Single numeric value giving the total population size used in the SIR model.
`recovery_rate` Single numeric value giving the recovery rate parameter of the SIR model.

Value

Named numeric vector: `ptran`, `crate`, `R0`.

`init_bilstm_model`*Initialize BiLSTM Model for SIR Parameter Estimation*

Description

Loads the trained BiLSTM model and associated scaler objects into memory. Requires that Python dependencies have been set up via [setup_python_deps](#).

Usage

```
init_bilstm_model(model_dir = NULL, force_reload = FALSE)
```

Arguments

`model_dir` Optional path to model directory. Defaults to the package's bundled model files.
`force_reload` Logical; reload even if already loaded.

Value

Invisibly returns TRUE on success.

`setup_python_deps`*Set up Python dependencies for epiworldRcalibrate*

Description

This function declares Python requirements through `\`reticulate\`` using `\`py_require()\`` (uv-backed in `reticulate` ≥ 1.41), then validates imports for all required modules (numpy, scikit-learn, joblib, PyTorch). Run this once after installing the package. This is kept separate from model functions so that package installation never happens automatically during normal use.

Usage

```
setup_python_deps(force = FALSE)
```

Arguments

<code>force</code>	Logical; if TRUE, resets package-managed Python requirements from a fresh R session. Default is FALSE.
--------------------	--

Details

The function performs the following steps:

1. Declares requirements with `reticulate::py_require()`.
2. Initializes Python through `reticulate`'s managed environment.
3. Verifies all packages can be imported.

Value

Invisibly returns TRUE on success.

Examples

```
## Not run:  
# First-time setup (run once after installing the package)  
setup_python_deps()  
  
# Force reinstall if something went wrong  
setup_python_deps(force = TRUE)  
  
## End(Not run)
```

utah_covid_data	<i>Utah COVID-19 epidemic trends</i>
-----------------	--------------------------------------

Description

Daily COVID-19 epidemic indicators for the state of Utah, obtained from the Utah Department of Health COVID-19 dashboard.

Usage

```
utah_covid_data
```

Format

A data frame with 365 rows and 5 variables:

Date Date of the observation (Date).

Daily.Cases Number of newly reported COVID-19 cases (numeric).

Smoothed.3.Day.Moving.Average Smoothed daily cases using a 3-day moving average (numeric).

X3.Day.Moving.Average Alternative 3-day moving average of daily cases (numeric).

Status Indicator of reporting or epidemic status (character or factor).

Source

Utah Department of Health COVID-19 Dashboard.

Examples

```
data("utah_covid_data")  
head(utah_covid_data)
```

Index

* datasets

- abc_calibration_params, 2
- utah_covid_data, 7

abc_calibration_params, 2

calibrate_sir, 3

check_model_status, 4

check_python_setup, 4

cleanup_model, 4

estimate_sir_parameters, 3, 5

init_bilstm_model, 3, 5

setup_python_deps, 5, 6

utah_covid_data, 7